



FUNCTION: 'HANDS FREE' RECOVERY OF 12mm TO 22mm LINE.

APPLICATION: DEVELOPED TO RECOVER LONG LINES OF TRAPS ON SMALLER VESSELS.

FEATURES: DECK HEAD MOUNTING REQUIRES MINIMUM SPACE.

ADJUSTABLE ROPE EXTRACTOR TO SET OPTIMUM GRIP AND COILING.

ROBUST GEARED PLANETARY REDUCTION DRIVE.

OPTIONAL, REMOVABLE WINCH DRUM FOR OFFLOADING THE CATCH.

SPECIFICATION:

CONTINUOUS LINE PULL: 2 TON

MINIMUM INSTALLED POWER: 55kW

NORMAL WORKING PRESSURE: 175 BAR

MAXIMUM WORKING PRESSURE: 210 BAR

MINIMUM RECOMMENDED OIL FLOW: 140 L/MIN

MAXIMUM OIL FLOW: 200 L/MIN

RECOMMENDED HYDRAULIC SYSTEM: OPEN CIRCUIT WITH RCP CONTROLLER

MERIDIAN TECHNOLOGIES	46 Milner Road Metro Industria Cape Town	P O Box 407 Milnerton 7435	CLIENT Meridian Technologies	A4	JOB No. - SCALE -	PAGE 1
	Tel: +27 21 510 1500 Fax: +27 21 510 1777		DESCRIPTION Deck Head Trap Hauler		DATE - DRAWN NW	OF 1

TLWDH Deckhead Trap Hauler in Operation



Line hauler with davit and open snatch block stored in the retracted position



The overhead mounting arrangement allows the recovered main line to coil conveniently below the hauler, considerably simplifying the handling of the gear